



OMEGA				
Code	Working Width (cm)	Transport Width (cm)	Weight (kg)	Tractor HP
LT1V 35	350	250	2050	80-120
LT1V 40	400	250	2100	100-140
LT1V 50	500	250	2200	120-180
LT1V 60	600	250	2600	160-210
LT1V 50 + AC	500	250	3510	120-180
LT1V 60 + AC	600	250	3680	160-210

All Data are not binding and subject to change without prior notice



SUBSOILER, Heavy Type

Code	No. Of Tines	Working width (mm)	Weight (kg)	Tractor HP
SBS X1	3	2700	1580	140-210
SBS X5	5	4500	1852	240-300

Optional Drawbar system
All Data are not binding and subject to change without prior notice



Gated Ejection Scraper

Code	Capacity (m³)	Working Width (mm)	Transport Width (mm)	Weight (kg)	Tractor HP
Turbo E-12	12	3300	3320	9200	250-300
Turbo E-15	15	3600	3680	10600	300-400
Turbo E-18	18	4300	4620	13100	375-500

All Data are not binding and subject to change without prior notice



SUBSOILER

Code	No. Of Tines	Working width (mm)	Weight (kg)	Tractor HP
SBS 3	3	1800	620	65-110
SBS 5	5	2500	820	110-130
SBS 7	7	3500	1250	130-150

All Data are not binding and subject to change without prior notice



LAND PLANE

Code	Working width (mm)	Transport Width (mm)	Transport Height (mm)	Length (mm)	Weight (Kg)	Tractor HP
LPL-100	4250	4250	2360	18250	4250	140-200

All Data are not binding and subject to change without prior notice



ILGI Agricultural Machinery
09260 Söke / AYDIN / TURKEY
T. +90 256 554 67 00 F. +90 256 554 60 07
www.ilgitirim.com info@ilgitirim.com

SUGARCANE IMPLEMENTS



For Better Farming





TANDEM DISC HARROW , Heavy Duty

Code	No. Of Disc	Working width (mm)	Transport Width (mm)	Disc Dia. (mm)	Disc Spacing (mm)	Weight (Kg)	Tractor HP
40 AGHX 56	40	4500	3200	560	230	5500	560-200
44 AGHX 56	44	5000	3200	560	230	5625	580-240
48 AGHX 56	48	5500	3200	560	230	5750	220-280
52 AGHX 56	52	6000	3200	560	230	6050	260-350

Optional : 610 mm and 660 mm Disc Diameter

Code	No. Of Disc	Working width (mm)	Transport Width (mm)	Disc Dia. (mm)	Disc Spacing (mm)	Weight (Kg)	Tractor HP
40 AGHX 71	40	4500	3200	710	300	7050	200-260
44 AGHX 71	44	5000	3200	710	300	7240	240-300
48 AGHX 71	48	5500	3200	710	300	7420	280-370
52 AGHX 71	52	6000	3200	710	300	7660	320-400

Optional : 760 mm Disc Diameter
All Data are not binding and subject to change without prior notice



OFFSET DISC HARROW , Heavy Duty

Code	No. Of Disc	Working width (mm)	Disc Dia. (mm)	Disc Spacing (mm)	Weight (Kg)	Tractor HP
14 AGH 91	14	2400	910	300	3255	180-240
16 AGH 91	16	2700	910	300	3415	240-300
18 AGH 91	18	3000	910	300	3615	280-320
20 AGH 91	20	3300	910	300	3795	300-350

All Data are not binding and subject to change without prior notice



DISC RIDGER

Code	Working width (mm)	Transport width (mm)	No. of gang	No. of Row	Row Space (mm)	Weight (Kg)	Tractor HP
DRG-2	3300-4200	4050	4	2	1800-1800	950	130-130
DRG-3	4200-5400	5750	6	3	1800-1800	1250	130-130

Optional : Fertilizer Unit Attachment with capacity 2 m³

All Data are not binding and subject to change without prior notice



DISC PLOUGH

Code	No. Of Disc	Working width (mm)	Weight (kg)	Tractor HP
DP-2	2	66	350	40-45
DP-3	3	99	450	50-60
DP-4	4	132	520	70-80
DP-5	5	165	590	100-120

All Data are not binding and subject to change without prior notice



RIDGE FLATTENER

Code	No. Of Disc	Width (mm)	Row Spacing (mm)	Weight (Kg)	Tractor HP
RF-2	2	2725	1300-1800	320	75-90
RF-3	3	4025	1300-1800	430	100-150



MOULDBOARD RIDGER

Code	No. Of Disc	Width (mm)	Row Spacing (mm)	Weight (Kg)	Tractor HP
MRB-2	2	3000	1300-1800	380	80-90
MRB-3	3	4500	1300-1800	480	120-150

All Data are not binding and subject to change without prior notice



GRAB LOADER

Maximum grapple height	5400mm
Maximum dumping height	5300mm
Engine Model	4BT3.9-C190
Rated Power	24kw/100HP
Engine Brand	Cummins
Total Machine Weight	2600kg
Grab Capacity	1200-1300 kg
Boom rotation Angle	120°
Overall dimension(LxWxH)	4900*2600*1100mm
Min. Ground Clearance	580mm

All Data are not binding and subject to change without prior notice



GRAB LOADER

Maximum grapple height	6200mm
Maximum grapple Radius	6200mm
Engine Model	4BT3.9-C215
Rated Power	2715HP
Engine Brand	Cummins
Grab Capacity	1500 kg
Working Efficiency	4000kg/min
Maximum Pushing Force	29KN
Boom rotation Angle	left and right 180 degree/ 360 degree continuous
Min. Ground Clearance	580mm

All Data are not binding and subject to change without prior notice



TRAILER

Capacity (m³ / Tonne)	10,000 kg / 10,000 kg	Up to 9000 kg	11,000 kg
Volumetric capacity	24 m³ (hect)	20 m³ (hect)	20 m³ (hect)
Length (mm)	4,380 mm	4,380 mm	5,000 mm
Trail length	7,110 mm	7,495 mm	7,520 mm
Width of equipment	3,186 mm	2,986 mm	3,200 mm
Height overfloor	4,700 mm	4,700 mm	5,096 mm
Loading height	3,540 mm	3,563 mm	4,000 mm
High rotation times	600/50 - 22.5°	600/50 - 22.5°	600/50 - 22.5°
Suspension	Tandem or leaf springs	Tandem	Tandem
Gauge	3,000 mm	3,000 mm	3,000 mm
Weight of equipment	8400 kg	7800 kg	9400 kg
Waterworks	85 L	85 L	85 L

All Data are not binding and subject to change without prior notice