



The working width is decreased for road security by folding the side batteries on transport position for our more than 40 discs offset types. The tractor power necessity is between 150-300hp according to number of discs. You can make your choice until 64 disc, 6.6 m working width according to your tractor power. Our machine that predominantly used on primary soil preparation is preferred by the farmers who have a big strong tractors. It can reach more working depth according to the soil conditions. You can make the processing more economical on preparation of seed bed for secondary product and stubble processing so your costs fall away. Especially it seems for the soil processing on big parcels and its working success reaches 40da/h with 8km/h related to model. It is a suitable machine for reduced soil processing and minimum soil processing that become important in the last years. It has more model alternatives with 22cm Disc spaces, 560mm – 610mm – 660mm disc diameters, plain and notched type discs. These alternatives enable to farmers for choosing the most suitable equipment for their own conditions. The disc direction angle that can be opened to 22 degree gets good soil working and also desired working depth. 2 pieces of land type tyres with the size 10.0/75 15.3 are used for each machines until 44 discs. For 44 discs and more 4 pieces of tyres are used.

HEAVY DUTY BEARING

The bearing chassis that tied to frame with rigid and a strong tine and bearing covers are produced with sensitive dimension on CNC bars as special cast iron. There are double 6215 bold bearings and 2 oil felts with double 50x80x13 seals inside. The strong structure of the bearings can resist to resistance while working on the soil. It had been provided a bearing without a problem when the casting quality, sensitive process and bearings integrated.



HYDRAULIC GANG ADJUSTMENT

The angle is altered mechanically with a series of holes and a locking pin. We can control the direction angels that effects to working depth, the properties of overturn and hatching, from the performed mechanism on the frame. In accordance with the demand this setting can be done by the help of hydraulic pistons.



RIGID AND ADJUSTABLE SCRAPER

Extremely strong and efficient scraper that resists wear cleans the discs and enhances the incorporation of residue. Scrapers are composed by steel chassis and the points that is in the suitable norm for disc concavity. Each scraper can be individually adjustable or move the entire gang of scrapers at the same time.



ADJUSTABLE DRAWBAR

Adjustable drawbar ensures a safe transport during road and solid pull of disc in field.



MEGASTAR-K

Heavy Duty Foldable Discharrow, Offset

Model	Number of Disc	Disc Dia (mm)	Working Width (cm)	Weight (kg)	Power* (HP)
40 AGB-K 56	40	560	420	2985	150 - 160
44 AGB-K 56	44	560	460	3088	170 - 180
48 AGB-K 56	48	560	500	3190	180 - 200
52 AGB-K 56	52	560	540	3294	200 - 210
56 AGB-K 56	56	560	580	3397	230 - 250
60 AGB-K 56	60	560	620	3515	270 - 290

Disc Spacing is (mm): 230

610 mm and 660 mm Disc Diameter models are optional

All Data are not binding and subject to change without prior notice

* Power Requirement may vary depending on soil conditions.

Ilgi Tarım Makinaları

09260 Söke - AYDIN /TURKEY

T: +90 256 554 67 00 F: +90 256 554 60 07

www.ilgitarim.com.tr • info@ilgitarim.com.tr



MEGASTAR-K

DISCHARROW



For Tractor From 150 to 290 Hp

IDEAL SOIL PREPARATION

ILGI

For Better Farming